IQ Series Fixtures

The Altman IQ Series™ is a range of PAR luminaires that deliver classsic style, efficiency, and versatility. With their lightweight spun and extruded aluminum construction, the rugged IQ Series boasts features like tool-free lamp access, vertical tilt lock with degree markings, and 370° horizontal rotation. All models have a durable powdercoat finish, available in standard black, white, or silver. Custom colors are also available. IQ Series fixtures come in a variety of sources:

- **CDM** designed for use with ceramic discharge metal halide (CDM) lamps, which are highly efficient, with long life and a high color rendering index.
- **Tungsten Halogen** these classic units provide proven performance – choose from hundreds of lamp options, including new generation LED replacement lamps.
- **Low Voltage** MR-16 and AR111 pinspot models with built-in dimmable electronic transformers.
- **LED** models designed with the latest technology for maximum life, and superior performance – available in color-changing or white light in various color temperatures. Custom LED mixes available.

The IQ Series — an ideal choice for all retail, display, exhibit, and residential applications.



IQWW



IQUV70



SSIQ38-RGBA

ARCHITECTURAL LIGHTING







IQ38C






IQ Series Fixtures

Features


- Rugged all-metal construction
- Wide range of light sources: Tungsten Halogen, Metal Halide, LED, Low Voltage
- Many track mount options, including the revolutionary Smart Track for independent control of each fixture
- A wide range of sizes: MR-16 through PAR64
- Smart versions allow dimming/switching via DMX
- Line Voltage, Low Voltage with electronic transformer, metal halide with ballast, LED with solid-state driver
- Standard and custom finishes
- ETL & cETL listed
- Proudly made in the USA



IQ Series Fixtures - Accssories and Mounting



SSIQ38 w/ Stem Mount



Typical Canopy Mount





4-Leaf Barndoor



Color Frame



Honeycomb Louver



Cross Baffle



510 Pipe Clamp



	(see fixture data sheets for details)
IQ20MR-* IQ20-* IQ20C-* IQ30C-* IQ36C-* IQ36C-* IQ38C-* IQ38C-* IQ38C-T6-* SSIQ38-* IQ56-* IQ64-* IQWW-* IQUV70-*	75W MR16 Architectural PAR 50W Architectural PAR 39W CDM Architectural PAR 75W Architectural PAR 39W or 70W CDM Architectural PAR 75W AR111 Architectural PAR Low Voltage Pin Spot 39W or 70W CDM Architectural Pin Spot 250W Canopy & Track / 90W Portable Architectural PAR 70W or 100W CDM Architectural PAR 70W or 150W T6 CDM Architectural PAR Spectra IQ38 50W LED Luminaire 500W Architectural PAR 500W Architectural PAR 500W Architectural PAR 200W IQ Wall Wash 70W Metal Halide IQ Series Blacklight

IQ SeriesFixtures

Factory Installed Mounting Options (add -suffix to part number)			
-Y	2-Circuit Smart Track adapter installed with DMX/RDM addressable Triac dimmer		
TLA-E166	Nordic Eco 1 Circuit Track Adapter		
TLA-TEK100	Nordic (Global) Spec Grade 2-Circuit Track Adapter		
TLA-GA100UL	Nordic (Global) Spec Grade 3-Circuit Track Adapter		
TLA-L	Lightolier Lytespan 1-Circuit Track Adapter		
TLA-H	Halo 1-Circuit Track Adapter		
TLA-J	Juno™ Track Adapter		
54-SVT183-24CC	Coiled Cord with Edison Connector—24" retracted, 6 foot extended - Factory installed		
Canopy	5" Diameter Canopy with universal mounting bracket		
Unistrut	Unistrut bracket installed—spring nuts by others		
Stem	Custom Stem to Canopy mount available—Max length 6'		

Additional Accessories (** indicates PAR fixture size - e.g., IQ30)		
IQ**-CH	Cylindrical Hood	
IQ**-SCH	Sparkle Cylindrical Hood	
IQ**-BD4	4 Leaf Barn Door	
IQ**-CF	Color Filter Holder	
IQ**-LV	1/4" Honeycomb Louver	
IQ**-SL	Prismatic Spread Lens	
IQ**-LSL	Linear Spread Lens	
IQ**-DGF-*	Dichroic Glass Filter *Specify Color	
IQ**-SGF-* IQ**-LBS-*	Slit Glass Filter *Specify Color	
IQ -LBS- IQ**-CB	Light Blocking Screen—* 20%, 30% or 40% Cross Baffle	
510-F	Light Duty Flat Steel Pipe Clamp: for 1/4" to 1-1/2" Pipe	
510-1	Malleable Iron Pipe Clamp: 3/4" to 1-1/2" Pipe,	
310	Lincludes 1/2" Bolt	
MEGA-CLAMP-*	Extruded Aluminum Clamp for 3/4" to 2" Pipe,	
WEO/ COL/ WII	includes 1/2" Bolt (*- Specify Black or Silver)	
MINI-CLAMP*	Extruded Aluminum Clamp for 1/2" to 1f 1/2" Pipe,	
	includes 3/8" Bolt (*- Specify Black or Silver)	
MICRO-CLAMP*	Extruded Aluminum Clamp for 3/8" to 1" Pipe,	
	includes 5/16" Bolt (*- Specify Black or Silver)	
	Accessory designs vary. Not all accessories are available for every fixture model. Refer to data sheets for specific fixtures or contact Altman Customer Service for more information.	