

## PEGASUS 6" LED FRESNEL

The Altman Pegasus 6 Fresnel is a 6-inch white output LED Fresnel that is both Mains Dimmable and DMX controlled all in one luminaire. Pegasus replicates the soft light output that is expected from a theatrical or studio fresnel. Under 150 Watts, the 6-inch Pegasus Fresnel far surpasses the output of its 500 watt incandescent counterpart.

Under Mains Dim Control these fresnels can plug directly into your theatrical phase-cut dimmers whether they are forward or reverse phase, and have been specially designed to replicate the smooth dimming curve of their incandescent twin. A 120/230 switch on the back of unit allows you to set the dimming curve for both 120 VAC and 230 VAC dimming systems.

If your lighting system consists of constant power and DMX data then Pegasus is also right choice for you. With the flip of a switch Pegasus converts from Mains Dimmable to a DMX / RDM controlled unit.


Pegasus is available in a number of different color temperatures from 2700K, 3000K, 4000K, and 5000K. Pegasus boasts a very high CRI, >90, and can be used with standard theatrical gel as well as gels that have been specifically formulated for LEDs.



*Pegasus6 Fresnel*

### **Product Features:**

- Delivers the output performance of a 500W Incandescent fresnel fixture
- 10,758 Lumens, LED and lens position dependent
- Mains Dimmable or DMX Controlled
- Available in both 6 and 8-inch models
- Available in four (4) different Color temperatures
- PowerCON & DMX in / thru connections
- Fully RDM Compliant when in DMX mode
- Electronic universal power supply 100-240VAC
- Fully homogenized beam
- High resolution digital dimming for both Mains Dimmable and DMX control
- 15 to 85 degree spot to flood beam spread
- 50,000 hours of life expectancy
- All metal construction
- Spot to flood focus adjustment
- C-Clamp, color frame, and safety cable included
- 11.5 lbs. / 5.22 kg. (including C-Clamp safety cable, and yoke)
- cETLus listed and CE marked for indoor use
- Made in the USA
- Five (5) year and one (1) day warranty
- No cost technical support for the life of your product



# Photometric Performance

*Spot @ 10  
Degrees*

Distance	(ft)	5.0	10.0	15.0	20.0	25.0	30.0	35.0	40.0	45.0
	(m)	1.5	3.0	4.6	6.1	7.6	9.1	10.7	12.2	13.7
Beam Diameter	(ft)	1' 3"	2' 5"	3' 7"	4' 10"	6'-7"	7'-11"	9'-2"	10'-6"	11'-10"
	(m)	0.4	0.7	1.1	1.5	2.0	2.4	2.8	3.2	3.6
2700K	(fc)	1455.0	363.7	161.7	90.9	58.2	40.4	29.7	22.7	18.0
	(lux)	15655.3	3913.8	1739.5	978.5	626.2	434.9	319.5	244.6	193.3
3000K	(fc)	1530.1	382.5	170.0	95.6	61.2	42.5	31.2	23.9	18.9
	(lux)	16463.6	4115.9	1829.3	1029.0	658.5	457.3	336.0	257.2	203.3
4000K	(fc)	1684.0	421.1	187.2	105.3	67.4	46.8	34.4	26.3	20.8
	(lux)	18119.8	4531.3	2013.8	1132.8	725.0	503.5	369.9	283.2	223.8
5000K	(fc)	1806.0	451.7	200.7	112.9	72.2	50.2	36.9	28.2	22.3
	(lux)	19432.6	4860.0	2160.0	1215.0	777.3	540.0	396.7	303.6	240.0

*Medium @ 35  
Degrees*

Distance	(ft)	5.0	10.0	15.0	20.0	25.0	30.0	35.0	40.0	45.0
	(m)	1.5	3.0	4.6	6.1	7.6	9.1	10.7	12.2	13.7
Beam Diameter	(ft)	2' 11"	6'-0"	9' 2"	11' 10"	17'-2"	20'-6"	24'-1"	27'-6"	30'-10"
	(m)	0.9	1.8	2.8	3.6	5.2	6.2	7.3	8.4	9.4
2700K	(fc)	581.5	145.4	64.6	36.3	23.3	16.2	11.9	9.1	7.2
	(lux)	6257.3	1564.3	695.3	391.1	250.3	173.8	127.7	97.8	77.3
3000K	(fc)	620.0	156.6	69.6	39.1	25.1	17.4	12.8	9.8	7.7
	(lux)	6671.2	1684.7	748.8	421.1	269.6	187.2	137.5	105.3	83.2
4000K	(fc)	685.5	171.4	76.2	42.8	27.4	19.0	14.0	10.7	8.5
	(lux)	7376.2	1844.0	819.6	461.0	295.0	204.9	150.5	115.3	91.1
5000K	(fc)	738.0	184.5	82.0	46.1	29.5	20.5	15.1	11.5	9.1
	(lux)	7941.2	1985.3	882.3	496.4	317.7	220.6	162.1	124.1	98.0

*Wide @ 50  
Degrees*

Distance	(ft)	5.0	10.0	15.0	20.0	25.0	30.0	35.0	40.0	45.0
	(m)	1.5	3.0	4.6	6.1	7.6	9.1	10.7	12.2	13.7
Beam Diameter	(ft)	6' 2"	11' 2"	17' 1"	21'	36'-3"	43'-6"	50'-9"	58'-2"	65'-4"
	(m)	1.9	3.4	5.2	6.4	11.0	13.3	15.5	17.7	19.9
2700K	(fc)	262.0	65.5	29.1	16.4	10.5	7.3	5.3	4.1	3.2
	(lux)	2819.1	704.8	313.2	176.1	112.8	78.3	57.5	44.0	34.8
3000K	(fc)	284.0	76.9	34.2	17.8	12.3	8.5	5.8	4.8	3.8
	(lux)	3055.8	827.0	367.6	191.1	132.3	91.9	62.4	51.7	40.8
4000K	(fc)	307.5	83.6	37.1	19.2	13.4	9.3	6.3	5.2	4.1
	(lux)	3308.3	899.2	399.6	206.8	143.9	99.9	67.5	56.2	44.4
5000K	(fc)	320.8	80.2	35.6	20.1	12.8	8.9	6.5	5.0	4.0
	(lux)	3451.5	862.8	383.5	215.7	138.1	95.9	70.4	53.9	42.6

# Specifications

<b>Materials:</b>	Corrosion-resistant materials and hardware
<b>Control:</b>	Mains dimmable or DMX/RDM
<b>Light Engine:</b>	130W LED Array - Available in 2700K, 3000K, 4000K, or 5000K
<b>Beam Lumens</b>	>10,758 Lumens, LED and lens position dependent
<b>CRI</b>	>90
<b>Rated LED Life:</b>	Array rating >50,000 hours to L70
<b>Input Voltage:</b>	100-240 VAC 50/60 Hz
<b>Power Factor</b>	> 0.92 @ Full Load (Mains Dimmable Models)
<b>Current Inrush</b>	15Apk Max 1/2 cycle @230VAC
<b>Quiescent Load</b>	12 Watts (DMX Models Only)
<b>LED Engine Cooling:</b>	Active, fan (<19dBa @ .5m)
<b>Environment:</b>	0 - 40°C (32 - 104°F) with humidity of 5-95% non-condensing)
<b>Weight:</b>	11.5 lbs. (5.22 kg) - including C-Clamp, safety cable, and yoke
<b>Body Color:</b>	Black standard, RAL colors available
<b>Compliance:</b>	cETLus listed for indoor use
<b>Warranty:</b>	Five (5) years and One (1) day
<b>Support:</b>	Supported Forever - free phone and online tech support for the life of your product.

Please note that noise levels on mains dim luminaires are subject to the dimming/switching systems in which they are wired. Electrical systems displaying harmonics may increase the audible noise output from the luminaire.

**IMPORTANT!** For fixtures that are mains dim controlled, do not connect more than four (4) luminaires to the same dimmer. Connecting more than four luminaires to the same dimmer will result in undesired low-end dimmer response. Note: dimmer must be sized appropriately to handle the luminaire load.



# Ordering Information

## PEG6-(LED ARRAY)-(BODY COLOR)

**Model** Pegasus6 6-inch LED Luminaire\*

**LED Array:** 2K (2700K), 3K (3000K), 4K (4000K) or 5K (5000K)

**Body Color:** Black (B) or White (W) or Custom (C)\*\*\*


*For custom colors, consult factory before ordering.*

# Included Accessories

<b>510</b>	Malleable Iron Pipe Clamp
<b>6-CF</b>	Color Frame
<b>SC-36-BK</b>	36-inch Black Safety Cable with Spring Clip
<b>PCL-PBG-12*</b>	5-foot 20A PowerCON with Edison Connector

# Optional Accessories

<b>6-BD-4</b>	4-Way Barn Door
<b>6-SN</b>	Snoot
<b>PCL-2P&amp;G-12-5-*</b>	5-foot 20A PowerCON with Stage Pin Connector
<b>PCL-TLG-12-5-*</b>	5-foot 20A PowerCON with L5-20P Twist-Lock Connector
<b>PCL-BARE-12-5-*</b>	5-foot 20A PowerCON with Bare End Lead
<b>PCTJ-12-5-*</b>	5-foot 20A PowerCON to PowerCON
<b>ST-PTO</b>	Eutrac (120V, two circuit) to PowerCON - power only adapter with luminaire track mounting hardware (only in black)
<b>ST-PDTP</b>	Smart Track (120V, two circuit) to PowerCON / 5-Pin XLR - Power and DMX adapter with luminaire track mounting hardware (only in black)



Altman Lighting  
 1400 East 66th Avenue  
 Denver, CO 80229 USA  
 +1 303 500-7072  
 sales@altmanlighting.com  
 support@altmanlighting.com

All specifications, descriptions, information, design, etc. contained in this document are subject to change without prior notice. All rights reserved.  
 10 June 2020 © 2020 Altman Stage Lighting, Inc.