

## Fixture Type:


A lightweight multi-purpose elliptical reflector floodlight. The 161 scoop produces a very diffuse soft edged beam of 20 feet in diameter at a distance of 10 feet. The 161 is designed to operate high color temperature tungsten halogen lamps. The luminaire is used in theatre and television as both a flood light and a cyclorama fixture. Other uses include photographic and television remote fill light. The scoop is an ideal fixture for color blending and for creating smooth even washes of light.


Specifications subject to change without notice

### 1 0 0 0 W A T T 16" SCOOP 161

Features

- · Heavy spun aluminum construction
- · Etched matte aluminum reflector
- · Two recessed single contact sockets
- · Wire mesh safety screen provided
- · Circular color frame available
- Three 36" Teflon lead wires
- · U.L. and c.U.L. listed for 1000 watts
- · Made in the USA







# **Specifications**

Housing: Spun steel construction.

Materials: Construction employs all corrosion-resistant materials and hardware.

Yoke: Rigid flat steel.

Reflector: Etched aluminum, matte finish, elliptical

design.

Socket: Recessed single contact, two provided.

Tool free relamping.


Rating: 120/240 volts AC/DC operation 8.3/4.2 amps, 1000 watts maximum.

Cable: 36" Teflon leads encased in black fiberglass

sleeving.

Finish: Baked black enamel.

W eight: Approx; 8 1/2 lbs. (3.83 kg.)



1	CCESSORIES plied with Luminaire				
161-CF	161–CF Color Frame, 16" Diameter w/ Safety Screen				

ADDITIONAL ACCESSORIES			
510 Malleable Iron Pipe Clamp SC Safety Cable with Spring clip			

### 161 SCOOP PERFORMANCE CHART WITH FCM LAMP

Candlepower	Beam Angle	Field Angle	Efficiency
(Candela)	(Degrees)	(Degrees)	(%)
28,000	43°	90°	80

#### LAMP DATA

	ANSI	Manufacturer	Color	Rated Life	Rated Cor	rection
Watts	Code	Lamp Code	Temp (°K)	(Hours)	Lumens F	actor
500		Q500 T3	3000	2000	10,800	.40
500	FDN	Q500 T3/4	3200	400	12,800	.47
750	DNT	Q750 T3/4	3000	400	19,500	.71
1000	FHM	Q1000 T3/4	3000	400	27,300	.98
1000	FCM	Q1000 T3/4CL	3200	400	28,000	1.00

