

# PHOENIX3 RGBL LED ZOOM

The 15°-35° and 30°-55° PHX LED Zoom profiles are state of the art luminaires in function, style, and efficiency. These zoom profiles have been designed and engineered with a number of innovative details and features enhancing versatility and efficiency without sacrificing performance.

PHX 3 is a 340 Watt (RGBL) Red, Green, Blue, and Lime Profile Spot outputting just over 10,000 Lumens which makes it a true front of house luminaire. A 360° rotating barrel and fully locking shutters help you keep the artistic part of your fixtures' focus intact with virtually no light leak.

The aesthetic appearance and ergonomically designed function controls only add to the appeal of the Phoenix3.

These new and innovative options are what makes the PHX LED profile ideal for theaters, special events, television studios, or wherever superior, energy efficient lighting performance is required.



*Phoenix3 30-55 Degree Zoom*

## Product Features:

- 360-degree rotating barrel
- >10,000 output lumens BrightAF engine
- Heat resistant Plano-Convex lensing
- Die-cast aluminum and sheet metal fabrication
- Color frame, C-Clamp, soft focus pattern holder, safety cable and 5 foot PowerCON included
- PowerCON in and out for daisy-chaining units - Up to 5 fixtures (20A Max) may be linked
- Available standard in Black or White
- Positive locking double-clutch fixture body
- Wide accessory slot with sliding cover for motorized pattern devices or optional iris
- Yoke made from rigid flat steel with dual locking handles, two mounting positions and indexed tilt angle markings
- DMX512 in/thru via 5-pin XLR connector
- Multiple on-board control options: color fades and strobes
- Console free stand alone Player Mode
- 8-bit or 16-bit virtual dimming engine provides smooth, high quality fades and minimizes color shift during dimming
- User friendly control interface
- Carries standard 5 year plus 1 day Altman Warranty
- 26.55 lbs. (12.02 kg.)
- cETLus listed and CE marked (IP20 Rated for indoor use)
- Assembled in the USA
- Five (5) year and one (1) day warranty
- No cost technical support for the life of your product

**Photometric Performance - PHX 3 RGBL with 15-35 Degree Zoom Lens****Narrow - 10716.35 Lumens**

Throw Distance (d)	10'	15'	20'	25'	30'	35'	40'	45'	50'	55'
	3.05m	4.57m	6.09m	7.62m	9.14m	10.67m	12.19m	13.72m	15.24m	16.76m
Beam Size Diameter	2' - 9"	3' - 11"	5'	6' - 2"	7' - 4"	8' - 6"	9' - 7"	10' - 9"	11' - 11"	13'
	0.85m	1.19m	1.54m	1.89m	2.24m	2.58m	2.93m	3.28m	3.63m	3.97m
Illuminance = fc (Illuminance = lux)	2909 (31312)	1293 (13917)	727 (7828)	465 (5010)	323 (3479)	237 (2556)	182 (1957)	144 (1546)	116 (1252)	96 (1035)

**Lens Medium - 10921.60 Lumens**

Throw Distance (d)	10'	15'	20'	25'	30'	35'	40'	45'	50'	55'
	3.05m	4.57m	6.09m	7.62m	9.14m	10.67m	12.19m	13.72m	15.24m	16.76m
Beam Size Diameter	4' - 3"	6' - 2"	8' - 1"	9' - 11"	11' - 10"	13' - 9"	15' - 7"	17' - 6"	19' - 5"	21' - 3"
	1.30m	1.88m	2.46m	3.03m	3.61m	4.18m	4.76m	5.34m	5.91m	6.49m
Illuminance = fc (Illuminance = lux)	1682 (18110)	748 (8049)	421 (4528)	269 (2898)	187 (2012)	137 (1478)	105 (1132)	83 (894)	67 (724)	56 (599)

**Lens Wide - 10682.52 Lumens**

Throw Distance (d)	10'	15'	20'	25'	30'	35'	40'	45'	50'	55'
	3.048m	4.572m	6.096m	7.62m	9.144m	10.668m	12.192m	13.716m	15.24m	16.764m
Beam Size Diameter	5' - 10"	8' - 6"	11' - 3"	13' - 11"	16' - 7"	19' - 3"	21' - 11"	24' - 7"	27' - 3"	29' - 11"
	1.79m	2.60m	3.42m	4.24m	5.05m	5.87m	6.69m	7.50m	8.32m	9.14m
Illuminance = fc (Illuminance = lux)	1129 (12151)	502 (5400)	282 (3038)	181 (1944)	125 (1350)	92 (992)	71 (759)	56 (600)	45 (486)	37 (402)

**Photometric Performance - PHX 3 RGBL with 30-55 Degree Zoom****Lens Narrow - 10598.7 Lumens**

Throw Distance (d)	10'	15'	20'	25'	30'	35'	40'	45'	50'	55'
	3.05m	4.57m	6.09m	7.62m	9.14m	10.67m	12.19m	13.72m	15.24m	16.76m
Beam Size Diameter	5' - 6"	8'	10' - 7"	13' - 1"	15' - 7"	18' - 1"	20' - 7"	23' - 2"	25' - 8"	28' - 2"
	1.69m	2.45m	3.22m	3.98m	4.75m	5.52m	6.28m	7.05m	7.82m	8.58m
Illuminance = fc (Illuminance = lux)	1030 (11086)	458 (4927)	257 (2771)	166 (1774)	114 (1232)	84 (905)	64 (693)	51 (547)	41 (443)	34 (366)


**Medium - 10762.82 Lumens**

Throw Distance (d)	10'	15'	20'	25'	30'	35'	40'	45'	50'	55'
	3.05m	4.57m	6.09m	7.62m	9.14m	10.67m	12.19m	13.72m	15.24m	16.76m
Beam Size Diameter	7' - 1"	10' - 5"	13' - 8"	17'	20' - 3"	23' - 7"	26' - 11"	30' - 2"	33' - 6"	36' - 9"
	2.16m	3.17m	4.17m	5.18m	6.18m	7.19m	8.19m	9.20m	10.20m	11.21m
Illuminance = fc (Illuminance = lux)	625 (6723)	278 (2988)	156 (1681)	100 (1076)	69 (747)	51 (549)	39 (420)	31 (332)	25 (269)	21 (222)

**Wide - 10883.21 Lumens**


Throw Distance (d)	10'	15'	20'	25'	30'	35'	40'	45'	50'	55'
	3.048m	4.572m	6.096m	7.62m	9.144m	10.668m	12.192m	13.716m	15.24m	16.764m
Beam Size Diameter	8' - 10"	13'	17' - 1"	21' - 3"	25' - 5"	29' - 7"	33' - 9"	37' - 10"	42'	46' - 2"
	2.68m	3.95m	5.22m	6.48m	7.75m	9.01m	10.28m	11.54m	12.81m	14.08m
Illuminance = fc (Illuminance = lux)	429 (4618)	191 (2052)	107 (1154)	69 (739)	48 (513)	35 (377)	27 (289)	21 (228)	17 (185)	14 (153)

Phoenix3 15-35 Degree Zoom



\*Dimensions shown are with shutter blades fully retracted (pushed in).

Phoenix3 30-55 Degree Zoom



\*Dimensions shown are with shutter blades fully retracted (pushed in).

## Specifications

<b>Materials:</b>	Corrosion-resistant materials and hardware
<b>Control:</b>	DMX/RDM
<b>Light Engine:</b>	85 RGBL LED Array
<b>Beam Lumens:</b>	>10,000 - See photometrics
<b>Rated LED Life:</b>	Array rating >50,000 hours to L70
<b>Input Voltage:</b>	100-240 VAC 50/60 Hz
<b>Watts:</b>	340
<b>Current Draw:</b>	2.83A at 120VAC / 1.47A at 230VAC
<b>Quiescent Load:</b>	0.087 AMP (10.54 Watts) @ 120 VAC* 0.045 AMP (10.54 Watts) @ 240 VAC* *Fan and display off
<b>Power Factor:</b>	≥ 0.95
<b>Power Through:</b>	Up to 5 Units at 120VAC* Up to 10 units at 230 VAC* * Recommended Power linking of units via powercon connection.
<b>LED Engine Cooling:</b>	Active with progressive output management.
<b>Environment:</b>	0 - 50°C (32 - 122°F) with humidity of 5-95% non-condensing)
<b>Weight:</b>	26.55 lbs. (12.04 kgs.)
<b>Body Color:</b>	Black or White
<b>Compliance:</b>	cETLus listed for indoor use and CE marked
<b>Warranty:</b>	Five (5) years and One (1) day
<b>Support:</b>	Supported Forever - free phone and online tech support for the life of your product.

### DMX VALUES FOR WHITE SETTINGS:

	RED	GREEN	BLUE	LIME	WATTS
3200K	100%	73%	63%	100%	193
4200K	100%	88%	72%	100%	230
5600K	100%	96%	84%	100%	267

*Note: There are many aftermarket accessories for Altman Lighting products available through third-party suppliers. When considering these aftermarket accessories, we suggest that you consult with your Altman Regional Sales Manager beforehand regarding capability and effects on product performance.*



## Ordering Information

### PHX3-(RGBL)-(LENS TYPE)-(FINISH COLOR)

<b>Model</b>	PHX3 (PHX 340W LED Profile Spot)
<b>LED Array:</b>	RGBL
<b>Lens Type:</b>	15Z (15°-35° zoom) or 30Z (30°-55° zoom) Black
<b>Body Color:</b>	(B) or White (W)

*Note: Each unit ordered includes a 7-1/2" x 7-1/2" Color Frame (6-CFB), C-Clamp (510), 36" Black Safety Cable (SC-36-BK), PHX Soft Focus Lens with A-Size Pattern Holder (PHX-SFLGSA), and 5-Foot AC Cable PowerCON to Edison (PCL-PBG-12-\*).*

## Accessories

<b>6-CFB</b>	Color Frame, 7-1/2" x 6-1/2"
<b>510</b>	Malleable Iron Pipe Clamp
<b>510-HD</b>	Heavy Duty Malleable Iron Pipe Clamp
<b>SC-36-BK</b>	36" Black Safety Cable with Spring Clamp
<b>6-DN</b>	7-1/2" x 7-1/2" Donut, Black with 3" Hole
<b>PDII</b>	Phoenix Drop In Iris
<b>PHX-SFLGSA</b>	PHX Soft Focus lens with A Size Pattern Holder
<b>PHX-PHGSA</b>	A Size Steel Pattern Holder (100mm OD / 75mm IA)
<b>PHX-PHGSA-B</b>	B Size Steel Pattern Holder (86mm OD / 64.5mm IA)
<b>PHX-PHGSA-B-GLS</b>	B Size Glass Pattern Holder (82mm OD / 64.5mm IA)
<b>PHX-PHGSA-B-GLS-86</b>	B Size Glass Pattern Holder (86mm OD / 64.5mm IA)
<b>PHX-PHISB</b>	B Size Steel Pattern Holder (86mm OD / 64.5mm IA) for Iris Slot
<b>PHX-PHISA-GLS</b>	A Size Glass Pattern Holder (100mm OD / 75mm IA) for Iris Slot
<b>PHX-PHISB-GLS</b>	B Size Glass Pattern Holder (82mm OD / 64.5mm IA) for Iris Slot
<b>PHX-PHISB-GLS-86</b>	B Size Glass Pattern Holder (86mm OD / 64.5mm IA) for Iris Slot
<b>PCL-PBG-12-*</b>	5' 20A PowerCON with Parallel Blade U Ground (Edison)
<b>PCL-2P&amp;G-12-5-*</b>	5' 20A PowerCON with 2P&G Stage Pin Connector, Male
<b>PCL-TLG-12-5-*</b>	5' 20A PowerCON with L5-20P Twist Locking Ground Connector, Male
<b>PCL-BARE-12-5-*</b>	5' 20A PowerCON with Bare End Lead

*Note: \*=W for White Cable, Black is standard and no suffix is required*