

Specifications

Materials: Corrosion-resistant materials and hardware

Control: DMX/RDM

Light Engine: 85 RGBL LED Array

Beam Lumens: >10,000 - See photometrics

Rated LED Life: Array rating >50,000 hours to L70

Input Voltage: 100-240 VAC 50/60 Hz

Watts: 340

Current Draw: 2.83A at 120VAC / 1.47A at 230VAC

Quiescent Load: 0.087 AMP (10.54 Watts) @ 120 VAC*
0.045 AMP (10.54 Watts) @ 240 VAC*
*Fan and display off

Power Factor: ≥ 0.95

Power Through: Up to 5 Units at 120VAC*
Up to 10 units at 230 VAC*
* Recommended Power linking of units via powercon connection.

LED Engine Cooling: Active with progressive output management.

Environment: 0 - 50°C (32 - 122°F) with humidity of 5-95% non-condensing)

Weight: 26.55 lbs. (12.04 kgs.)

Body Color: Black or White

Compliance: cETLus listed for indoor use and CE marked

Warranty: Five (5) years and One (1) day

Support: Supported Forever - free phone and online tech support for the life of your product.

DMX VALUES FOR WHITE SETTINGS:

	RED	GREEN	BLUE	LIME	WASH
3200K	100%	83%	63%	100%	100
4200K	100%	88%	72%	100%	200
5600K	100%	92%	84%	100%	267

Note: There are many aftermarket accessories for Altman Lighting products available through third-party suppliers. When considering these aftermarket accessories, we suggest that you consult with your Altman Regional Sales Manager beforehand regarding capability and effects on product performance.



Ordering Information

PHX3-(RGBL)-(LENS TYPE)-(FINISH COLOR)

Model: PHX3 (PHX 340W LED Profile Spot)

LED Array: RGBL

Lens Type: 15Z (15°-35° zoom) or 30Z (30°-55° zoom) Black

Body Color: (B) or White (W)

Note: Each unit ordered includes a 7-1/2" x 7-1/2" Color Frame (6-CFB), C-Clamp (510), 36" Black Safety Cable (SC-36-BK), PHX Soft Focus Lens with A-Size Pattern Holder (PHX-SFLGSA), and 5-Foot AC Cable PowerCON to Edison (PCL-PBG-12-)*

Accessories

- 6-CFB** Color Frame, 7-1/2" x 7-1/2"
- 510** Malleable Iron Pipe Clamp
- 510-HD** Heavy Duty Malleable Iron Pipe Clamp
- SC-36-BK** 36" Black Safety Cable with Spring Clamp
- 6-IN** 7-1/2" x 7-1/2" Lens Back with 3" Hole
- FDI** Phoenix Drop In Iris
- PHX-SFLGSA** PHX soft focus lens with A Size Pattern Holder
- PHX-PHGSA** A Size Steel Pattern Holder (100mm OD / 75mm IA)
- PHX-PHGSP** A Size Steel Pattern Holder (86mm OD / 64.5mm IA)
- PHX-PHGSP-GLS** B Size Glass Pattern Holder (82mm OD / 64.5mm IA)
- PHX-PHGSP86-GLS** B Size Glass Pattern Holder (86mm OD / 64.5mm IA)
- PHX-PHISB** B Size Steel Pattern Holder (86mm OD / 64.5mm IA) for Iris Slot
- PHX-PHISA-GLS** A Size Glass Pattern Holder (100mm OD / 75mm IA) for Iris Slot
- PHX-PHISB-GLS** B Size Glass Pattern Holder (82mm OD / 64.5mm IA) for Iris Slot
- PHX-PHIS86-GLS** B Size Glass Pattern Holder (86mm OD / 64.5mm IA) for Iris Slot
- PCL-PBG-12-*** 5' 20A PowerCON with Parallel Blade U Ground (Edison)
- PCL-2P&G-12-5-*** 5' 20A PowerCON with 2P&G Stage Pin Connector, Male
- PCL-TLG-12-5-*** 5' 20A PowerCON with L5-20P Twist Locking Ground Connector, Male
- PCL-BARE-12-5-*** 5' 20A PowerCON with Bare End Lead

*Note: *=W for White Cable, Black is standard and no suffix is required*



Altman Lighting
1400 East 66th Avenue
Denver, CO 80229 USA
+1 303 500-7072
sales@altmanlighting.com
support@altmanlighting.com

14 January 2022 © 2022 Altman Stage Lighting, Inc.
All specifications, descriptions, information, design, etc. contained in this document are subject to change without prior notice. All rights reserved.